



HyperRough Cubic Set and SuperhyperRough Cubic Set

Takaaki Fujita^{1,*}

¹ Independent Researcher, Shinjuku, Shinjuku-ku, Tokyo, Japan

Email: takaaki.fujita060@gmail.com

Received: January 28, 2024 Revised: March 27, 2024 Accepted: June 30, 2024 ★ Corresponding author

ABSTRACT

Rough sets provide a mathematical framework for approximating subsets using lower and upper bounds determined by equivalence relations, effectively modeling uncertainty in classification and data analysis. These foundational concepts have been further extended to structures such as Hyperrough Sets and Superhyperrough Sets. In this paper, we introduce the definitions of Hyperrough Cubic Sets and Superhyperrough Cubic Sets, and explore their fundamental properties. We hope that these developments will promote further research into applications such as decision-making based on Rough Set Theory and its extensions.

Keywords: Rough set ▪ Hyperrough Set ▪ Rough Cubic Set ▪ SuperHyperRough Set

1. PRELIMINARIES AND DEFINITIONS

This section provides an introduction to the foundational concepts and definitions required for the discussions in this paper. Throughout this study, all sets are assumed to be finite.

1.1 Rough Set, HyperRough Set, and Superhyperrough Set

A rough set approximates a subset using lower and upper bounds determined by equivalence classes, thereby capturing both certainty and uncertainty in membership [1, 3, 6, 8, 11, 13]. The following definitions formalize these concepts.

Definition 1.1 (Rough Set Approximation). Let X be a nonempty universe of discourse, and let $R \subseteq X \times X$ be an equivalence relation (also called an indiscernibility relation) on X [12]. The relation R partitions X into disjoint equivalence classes, denoted by $[x]_R$ for each $x \in X$, where

$$[x]_R = \{y \in X \mid (x, y) \in R\}.$$

For any subset $U \subseteq X$, the lower approximation $\underline{U}$ and the upper approximation $\overline{U}$ are defined by:

1. Lower Approximation:

$$\underline{U} = \{x \in X \mid [x]_R \subseteq U\}.$$

This set contains all elements whose entire equivalence class is contained within U ; these elements *definitely* belong to U .

2. Upper Approximation:

$$\overline{U} = \{x \in X \mid [x]_R \cap U \neq \emptyset\}.$$

This set contains all elements whose equivalence class has a nonempty intersection with U ; these elements *possibly* belong to U .

Thus, the pair $(\underline{U}, \overline{U})$ forms the rough set representation of U , satisfying

$$\underline{U} \subseteq U \subseteq \overline{U}.$$

The *HyperRough Set* extends rough set theory by incorporating multiple attributes. Related foundations and hybrid rough–hypersoft constructions are discussed in [5, 6, 7, 8, 9].

Definition 1.2 (HyperRough Set). Let X be a nonempty finite universe, and let $T_1, T_2, \dots, T_n$ be n distinct attributes with

corresponding domains $J_1, J_2, \dots, J_n$. Define the Cartesian product

$$J = J_1 \times J_2 \times \dots \times J_n.$$

Let $R \subseteq X \times X$ be an equivalence relation on X , with $[x]_R$ denoting the equivalence class of x . A *HyperRough Set* over X is a pair (F, J) , where:

- $F : J \rightarrow \mathcal{P}(X)$ is a mapping that assigns to each attribute value combination $a = (a_1, a_2, \dots, a_n) \in J$ a subset $F(a) \subseteq X$.
- For each $a \in J$, the rough set approximations of $F(a)$ are defined as

$$\begin{aligned} \underline{F(a)} &= \{x \in X \mid [x]_R \subseteq F(a)\}, \\ \overline{F(a)} &= \{x \in X \mid [x]_R \cap F(a) \neq \emptyset\}. \end{aligned}$$

Here, $\underline{F(a)}$ comprises all elements whose equivalence classes are completely contained within $F(a)$, while $\overline{F(a)}$ contains elements whose equivalence classes intersect $F(a)$. Additionally, the following properties hold for all $a \in J$:

- $\underline{F(a)} \subseteq \overline{F(a)}$.
- If $F(a) = \emptyset$, then $\underline{F(a)} = \overline{F(a)} = \emptyset$.
- If $F(a) = X$, then $\underline{F(a)} = \overline{F(a)} = X$.

Example 1.3 (HyperRough Set). Let

$$X = \{x_1, x_2, x_3, x_4\}$$

be a finite universe and define an equivalence relation $R \subseteq X \times X$ by

$$[x_1]_R = \{x_1, x_2\} \quad \text{and} \quad [x_3]_R = \{x_3, x_4\}.$$

Let T_1 and T_2 be two attributes with domains

$$J_1 = \{\text{red}, \text{blue}\} \quad \text{and} \quad J_2 = \{\text{circle}, \text{square}\},$$

respectively. Then the Cartesian product is

$$J = J_1 \times J_2 = \{(\text{red}, \text{circle}), (\text{red}, \text{square}), (\text{blue}, \text{circle}), (\text{blue}, \text{square})\}.$$

Define a mapping

$$F : J \rightarrow \mathcal{P}(X)$$

by setting:

$$\begin{aligned} F(\text{red}, \text{circle}) &= \{x_1, x_2\}, \\ F(\text{red}, \text{square}) &= \{x_1\}, \\ F(\text{blue}, \text{circle}) &= \{x_3, x_4\}, \\ F(\text{blue}, \text{square}) &= \emptyset. \end{aligned}$$

For each $a \in J$, the rough approximations of $F(a)$ are given by

$$\begin{aligned} \underline{F(a)} &= \{x \in X \mid [x]_R \subseteq F(a)\}, \\ \overline{F(a)} &= \{x \in X \mid [x]_R \cap F(a) \neq \emptyset\}. \end{aligned}$$

For instance, for $a = (\text{red}, \text{circle})$ we have $F(\text{red}, \text{circle}) = \{x_1, x_2\}$. Since for each $x \in \{x_1, x_2\}$ the equivalence class $[x]_R$

(which equals $\{x_1, x_2\}$) is entirely contained in $F(\text{red}, \text{circle})$, it follows that

$$\underline{F(\text{red}, \text{circle})} = \overline{F(\text{red}, \text{circle})} = \{x_1, x_2\}.$$

Thus, (F, J) constitutes a HyperRough Set over X .

Definition 1.4 (*n*-SuperHyperRough Set). Let X be a nonempty finite universe, and let $T_1, T_2, \dots, T_n$ be n distinct attributes with respective domains $J_1, J_2, \dots, J_n$. For each attribute T_i , let $\mathcal{P}(J_i)$ denote its power set. Define the set of all possible attribute value combinations as

$$J = \mathcal{P}(J_1) \times \mathcal{P}(J_2) \times \dots \times \mathcal{P}(J_n).$$

Let $R \subseteq X \times X$ be an equivalence relation on X . An *n*-SuperHyperRough Set over X is a pair (F, J) , where:

- $F : J \rightarrow \mathcal{P}(X)$ is a mapping that assigns to each attribute value combination $A = (A_1, A_2, \dots, A_n) \in J$ (with $A_i \subseteq J_i$ for all i) a subset $F(A) \subseteq X$.
- For each $A \in J$, the lower and upper approximations are defined as

$$\begin{aligned} \underline{F(A)} &= \{x \in X \mid [x]_R \subseteq F(A)\}, \\ \overline{F(A)} &= \{x \in X \mid [x]_R \cap F(A) \neq \emptyset\}. \end{aligned}$$

Thus, $\underline{F(A)}$ consists of all elements whose equivalence classes are entirely contained in $F(A)$, and $\overline{F(A)}$ includes those elements whose equivalence classes intersect $F(A)$. The following properties hold for all $A \in J$:

- $\underline{F(A)} \subseteq \overline{F(A)}$.
- If $F(A) = \emptyset$, then $\underline{F(A)} = \overline{F(A)} = \emptyset$.
- If $F(A) = X$, then $\underline{F(A)} = \overline{F(A)} = X$.
- For any $A, B \in J$,

$$\begin{aligned} \underline{F(A \cap B)} &\subseteq \underline{F(A)} \cap \underline{F(B)}, \\ \overline{F(A \cup B)} &\supseteq \overline{F(A)} \cup \overline{F(B)}. \end{aligned}$$

Example 1.5 (*n*-SuperHyperRough Set). Let

$$X = \{x_1, x_2, x_3\}$$

and consider the equivalence relation $R \subseteq X \times X$ defined by

$$[x_1]_R = \{x_1, x_2\} \quad \text{and} \quad [x_3]_R = \{x_3\}.$$

Let T_1 be an attribute with domain

$$J_1 = \{\text{red}, \text{blue}\}.$$

Then the power set of J_1 is

$$\mathcal{P}(J_1) = \{\emptyset, \{\text{red}\}, \{\text{blue}\}, \{\text{red}, \text{blue}\}\}.$$

Define a mapping

$$F : \mathcal{P}(J_1) \rightarrow \mathcal{P}(X)$$

by:

$$\begin{aligned} F(\emptyset) &= \emptyset, \\ F(\{\text{red}\}) &= \{x_1\}, \\ F(\{\text{blue}\}) &= \{x_2, x_3\}, \\ F(\{\text{red}, \text{blue}\}) &= X. \end{aligned}$$

For each $A \in \mathcal{P}(J_1)$, the rough approximations are given by

$$\begin{aligned} \underline{F}(A) &= \{x \in X \mid [x]_R \subseteq F(A)\}, \\ \overline{F}(A) &= \{x \in X \mid [x]_R \cap F(A) \neq \emptyset\}. \end{aligned}$$

Consider $A = \{\text{red}\}$ so that $F(\{\text{red}\}) = \{x_1\}$. Since $[x_1]_R = \{x_1, x_2\}$ is not a subset of $\{x_1\}$, we have

$$\underline{F}(\{\text{red}\}) = \emptyset.$$

However, as $[x_1]_R \cap \{x_1\} \neq \emptyset$ and $[x_2]_R = \{x_1, x_2\}$ also intersects $\{x_1\}$, it follows that

$$\overline{F}(\{\text{red}\}) = \{x_1, x_2\}.$$

Thus, the pair $(F, \mathcal{P}(J_1))$ defines an n -SuperHyperRough Set (with $n = 1$) over X .

1.2 Rough Cubic Sets

The concept of cubic sets has been extensively studied in various contexts such as fuzzy and neutrosophic frameworks [4, 10, 14]. Similarly, research has also been conducted on the application of cubic sets within rough set theory [2]. We present the formal definition of Rough Cubic Sets below.

Definition 1.6 (Rough Cubic Sets). Let X be a nonempty set and let

$$R = \langle R, r \rangle : X \times X \rightarrow ([0, 1] \times [0, 1])$$

be a *cubic relation* on X . A cubic set on X is given by a mapping

$$A = \langle A, \lambda \rangle : X \rightarrow ([0, 1] \times [0, 1]),$$

where for each $x \in X$, $A(x)$ (or equivalently, $\langle A(x), \lambda(x) \rangle$) represents the membership degree of x in an interval-valued and crisp manner.

Using the cubic relation R , we define two *rough operators* on cubic sets as follows. For every cubic set $A = \langle A, \lambda \rangle$ on X , define the lower rough approximation $N(A)$ and the upper rough approximation $H(A)$ by

$$N(A)(x) = \bigcup_{y \in X} (A(y) t R^c(y, x)), \quad \forall x \in X,$$

$$H(A)(x) = \bigcap_{y \in X} (A(y) u R(x, y)), \quad \forall x \in X.$$

Here, t denotes a chosen t-norm (e.g., the minimum operation), u denotes the corresponding t-conorm (e.g., the maximum operation), and R^c represents the complement of the cubic relation R .

If $N(A) = H(A)$ (that is, if the lower and upper approximations coincide), then A is called a *definable cubic set*. Otherwise, A is termed *undefinable*, and the pair $(N(A), H(A))$ is referred to as a *rough cubic set*.

2. RESULTS OF THIS PAPER

This section presents the results obtained in this paper.

2.1 Hyperrough Cubic Sets

We provide the definition of Hyperrough Cubic Sets as follows.

Definition 2.1 (Hyperrough Cubic Set). Let X be a nonempty set and let

$$R = \langle R, r \rangle : X \times X \rightarrow ([0, 1] \times [0, 1])$$

be a cubic relation on X . Denote by $CS(X)$ the collection of all cubic sets on X (each cubic set A being given by a mapping $A = \langle A, \lambda \rangle : X \rightarrow ([0, 1] \times [0, 1])$). Let J be a nonempty set (interpreted as an index set of attribute value combinations). A *Hyperrough Cubic Set* over X is defined as a mapping

$$F : J \rightarrow CS(X).$$

For each $a \in J$, denote $A_a = F(a)$ and define the lower and upper rough approximations of A_a with respect to the cubic relation R by

$$N(A_a)(x) = \bigcup_{y \in X} (A_a(y) t R^c(y, x)), \quad \forall x \in X,$$

$$H(A_a)(x) = \bigcap_{y \in X} (A_a(y) u R(x, y)), \quad \forall x \in X,$$

where t is a chosen t-norm (for instance, the minimum operation), u is the corresponding t-conorm (for instance, the maximum operation), and R^c denotes the complement of the cubic relation R .

The pair $(N(A_a), H(A_a))$ constitutes the rough approximation of the cubic set A_a . Thus, the structure (F, J) is called a *Hyperrough Cubic Set* on X .

Example 2.2 (Hyperrough Cubic Set Example). Let $X = \{x_1, x_2, x_3\}$ and suppose a cubic relation $R = \langle R, r \rangle$ on X is given (for simplicity, assume that for each pair (x_i, x_j) , $R(x_i, x_j)$ provides an interval and a crisp value). Let $J = \{a\}$ be a singleton index set. Define a cubic set A on X by

$$A(x_1) = ([0.3, 0.7], 0.5),$$

$$A(x_2) = ([0.4, 0.8], 0.6),$$

$$A(x_3) = ([0.2, 0.6], 0.4).$$

Then define the hyperrough cubic set $F : J \rightarrow CS(X)$ by setting $F(a) = A$. The rough approximations $N(A)$ and $H(A)$ are computed from A using the operators

$$N(A)(x) = \bigcup_{y \in X} (A(y) t R^c(y, x)),$$

$$H(A)(x) = \bigcap_{y \in X} (A(y) u R(x, y)).$$

Thus, $(F, \{a\})$ constitutes a Hyperrough Cubic Set that, by definition, generalizes the rough cubic set $(N(A), H(A))$ and, if the cubic structure were degenerate, would coincide with a hyperrough set.

Theorem 2.3. A Hyperrough Cubic Set generalizes both Rough Cubic Sets and Hyperrough Sets.

Proof. If the index set J is a singleton (say, $J = \{a_0\}$), then the mapping F reduces to $F(a_0) = A_{a_0}$, and the Hyperrough Cubic Set (F, J) becomes the rough cubic set $(N(A_{a_0}), H(A_{a_0}))$ induced by the cubic relation R .

Conversely, if the cubic structure degenerates (i.e., if the secondary component of each cubic set is constant so that every cubic set reduces to an interval-valued fuzzy set), then the rough approximations $N(A_a)$ and $H(A_a)$ coincide with those defined for hyperrough sets. Hence, a Hyperrough Cubic Set encompasses both rough cubic sets (when J is trivial) and hyperrough sets (when the cubic structure is degenerate). $\square$

2.2 n -Superhyperrough Cubic Sets

We provide the definition of n -Superhyperrough Cubic Sets as follows.

Definition 2.4 (n -Superhyperrough Cubic Set). Let X be a nonempty set and let

$$R = \langle R, r \rangle : X \times X \rightarrow ([0, 1] \times [0, 1])$$

be a cubic relation on X . Suppose that $T_1, T_2, \dots, T_n$ are n distinct attributes with respective domains $J_1, J_2, \dots, J_n$. Define the attribute domain as

$$J = \mathcal{P}(J_1) \times \mathcal{P}(J_2) \times \dots \times \mathcal{P}(J_n),$$

where $\mathcal{P}(J_i)$ denotes the power set of J_i . An n -Superhyperrough Cubic Set over X is defined as a mapping

$$F : J \rightarrow CS(X),$$

such that for each $A = (A_1, A_2, \dots, A_n) \in J$, if we denote $A_A = F(A)$ and define its lower and upper rough approximations (with respect to the cubic relation R) by

$$N(A_A)(x) = \bigcup_{y \in X} (A_A(y) t R^c(y, x)), \quad \forall x \in X,$$

$$H(A_A)(x) = \bigcap_{y \in X} (A_A(y) u R(x, y)), \quad \forall x \in X,$$

then the pair $(N(A_A), H(A_A))$ constitutes the rough approximation of the cubic set A_A . The structure (F, J) is called an n -Superhyperrough Cubic Set on X .

Example 2.5 (n -Superhyperrough Cubic Set). Let $X = \{x_1, x_2, x_3, x_4\}$ and let $R = \langle R, r \rangle$ be a given cubic relation on X . Assume there are two attributes T_1 and T_2 with domains $J_1 = \{p, q\}$ and $J_2 = \{r, s\}$, respectively. Then, define the attribute domain as

$$J = \mathcal{P}(J_1) \times \mathcal{P}(J_2).$$

For instance, an element of J could be $A = (\{p\}, \{r, s\})$. For each $A \in J$, define a cubic set A_A on X ; for example, let

$$A_{(\{p\}, \{r, s\})}(x_1) = ([0.2, 0.5], 0.4),$$

$$A_{(\{p\}, \{r, s\})}(x_2) = ([0.3, 0.6], 0.5),$$

and similarly define $A_{(\{p\}, \{r, s\})}(x_3)$ and $A_{(\{p\}, \{r, s\})}(x_4)$. Then, define the mapping

$$F : J \rightarrow CS(X)$$

by setting $F(A) = A_A$ for each $A \in J$. For every $A \in J$, compute the lower and upper rough approximations $N(A_A)$ and $H(A_A)$ using the cubic relation R . The pair (F, J) is then an n -Superhyperrough Cubic Set on X , which, by our previous theorem, generalizes both the Hyperrough Cubic Set and the n -Superhyperrough Set.

Theorem 2.6. An n -Superhyperrough Cubic Set generalizes both Hyperrough Cubic Sets and n -Superhyperrough Sets.

Proof. If we restrict the attribute domain J to a singleton (i.e., when each J_i is a singleton so that J itself is a singleton), then the mapping F reduces to a mapping into $CS(X)$, and the n -Superhyperrough Cubic Set reduces to a Hyperrough Cubic Set.

Alternatively, if the cubic structure is degenerate (so that every cubic set becomes an interval-valued fuzzy set), then the mapping $F : J \rightarrow CS(X)$ effectively maps into the collection of fuzzy sets, and the rough approximations coincide with those defined for n -Superhyperrough Sets. Thus, an n -Superhyperrough Cubic Set encompasses both Hyperrough Cubic Sets and n -Superhyperrough Sets. $\square$

ACKNOWLEDGMENTS

We extend our sincere gratitude to everyone who provided insights, inspiration, and assistance throughout this research. We particularly thank our readers for their interest and acknowledge the authors of the cited works for laying the foundation that made our study possible. We also appreciate the support from individuals and institutions that provided the resources and infrastructure needed to produce and share this paper. Finally, we are grateful to all those who supported us in various ways during this project.

DISCLAIMER (LIMITATIONS AND CLAIMS)

The theoretical concepts presented in this paper have not yet been subject to practical implementation or empirical validation. Future researchers are invited to explore these ideas in applied or experimental settings. Although every effort has been made to ensure the accuracy of the content and the proper citation of sources, unintentional errors or omissions may persist. Readers should independently verify any referenced materials.

To the best of the authors' knowledge, all mathematical statements and proofs contained herein are correct and have been thoroughly vetted. Should you identify any potential errors or ambiguities, please feel free to contact the authors for clarification.

The results presented are valid only under the specific assumptions and conditions detailed in the manuscript. Extending these findings to broader mathematical structures may require additional research. The opinions and conclusions expressed in this work are those of the authors alone and do not necessarily reflect the official positions of their affiliated institutions.

REFERENCES

- [1] S. Broumi, F. Smarandache, and M. Dhar, "Rough neutrosophic sets," *Infinite Study*, vol. 32, pp. 493–502, 2014.

-
- [2] X. Chen, “On rough cubic sets,” *Annals of Fuzzy Mathematics and Informatics*, vol. 21, no. 3, pp. 319–331, 2021.
 - [3] Y. Chen, D. Miao, R. Wang, and K. Wu, “A rough set approach to feature selection based on power set tree,” *Knowledge-Based Systems*, vol. 24, no. 2, pp. 275–281, 2011.
 - [4] V. Chinnadurai, S. Thayalan, and A. Bobin, “Complex cubic set and their properties,” *Advances in Mathematics: Scientific Journal*, vol. 9, no. 4, pp. 1561–1567, 2020.
 - [5] F. Smarandache, M. Saeed, M. Saqlain, and M. Abdel-Baset, *Theory and Application of Hypersoft Set*. Brussels: Pons Publishing House, 2021.
 - [6] H. Kamacı, “On hybrid structures of hypersoft sets and rough sets,” *International Journal of Modern Science and Technology*, vol. 6, no. 4, pp. 69–82, 2021.
 - [7] V. S. Subha and R. Selvakumar, “A new approach to neutrosophic hypersoft rough sets,” *Neutrosophic Sets and Systems*, vol. 58, no. 1, pp. 226–247, 2023.
 - [8] A. U. Rahman, A. Hafeez, M. Saeed, M. R. Ahmad, and U. Farwa, “Development of rough hypersoft set with application in decision making for the best choice of chemical material,” *Theory and Application of Hypersoft Set*, pp. 192–202, 2021.
 - [9] S. Y. Musa, R. A. Mohammed, and B. A. Asaad, “ N -hypersoft sets: An innovative extension of hypersoft sets and their applications,” *Symmetry*, vol. 15, no. 9, p. 1795, 2023.
 - [10] J. G. Lee, G. Senel, J. Kim, D. H. Yang, and K. Hur, “Cubic crisp sets and their application to topology,” *Annals of Fuzzy Mathematics and Informatics*, vol. 21, no. 3, pp. 227–265, 2021.
 - [11] Z. Pawlak, “Rough sets,” *International Journal of Computer & Information Sciences*, vol. 11, pp. 341–356, 1982.
 - [12] Z. Pawlak, “Rough set theory and its applications to data analysis,” *Cybernetics & Systems*, vol. 29, no. 7, pp. 661–688, 1998.
 - [13] Z. Pawlak and A. Skowron, “Rudiments of rough sets,” *Information Sciences*, vol. 177, no. 1, pp. 3–27, 2007.
 - [14] T. Senapati, Y. B. Jun, and K. P. Shum, “Cubic set structure applied in UP-algebras,” *Discrete Mathematics, Algorithms and Applications*, vol. 10, no. 04, p. 1850049, 2018.
-